

SL490

Lobby ATM

wincash series



- > *Small footprint and full functionality*
- > *Banknotes withdrawal an Web-ATM functions*
- > *Optimized cash management*
- > *High resolution 15" TFT LCD colour screen*
- > *Capabillities to play advertisement with full motion video*
- > *Industry Standard CEN/XFS architecture*
- > *User friendly interface, ADA, CAE, CSA and Co.Ge.Ban compliant*
- > *Multimedia kit for visually impaired people*
- > *A4 document printer and Barcode reader version available*
- > *ISO and EMV security compliance with antiskimming and card protection technology*



Kharazmi
IT Development Inc.

www.kharazmico.com

TECHNICAL SPECIFICATIONS

USER INTERFACE	CONTROL UNIT
15" TFT LCD color display normal or high luminosity with tamper proof panel	"Intel Pentium IV" or equivalent with DVD and FD
Touch Screen	SOFTWARE ENVIRONMENT
Privacy Display Filter	Microsoft® Windows® XP Professional
8 (4+4) function display keys with integrated led and tactile feedback	SOFTWARE
EPP (Encryption Pin Pad) 16 tamper proof keys (3DES, RSA and Remote Key Loading) PCI certified Compliant with: ISO 9564-1, ISO 13491, ISO 13491-2 and ECBS standard	Middleware: XFS Manager NDC and DDC 91X emulators ISO 8583 WCash-SIA network interface Self Service Banking SW Graphic advertisement SW InfoQul SW Web ATM
Tamper proof QWERTY keyboard with or without Track-ball	Network interface SW: VISA - Europay - Cirrus - Mastercard - Eurocard - Cash Advance - Others
Motorized hybrid badge reader/writer magnetic/microchip (ISO7812/ISO7816) EMV 3.1.1. and 4.0 level 1 certified Card Return on Power Fall Antiskimming jitter (micromovement) Led crown for badge entrance Security sensors for fraud detection Held badge box	Electronic Log with remote transfer SW Distribution
Lighting indicators guide identifying the active peripheral	OPERATOR INTERFACE
BARCODE READER	15" TFT LCD color display + keyboard
BANKNOTES DISPENSER 1 to 4 cassettes on-site configurable capacity 3000 banknotes each 1 Divert / Retract cassette with separator Staining device, antiexplosive and gas detection device compliant Special design for easy sealing	NETWORKING
PRINTERS 40 column graphics thermal receipt printer paper width 80mm with cutter and sensor for end and near to end paper	TCP/IP, SNA/SDLC, X25, Telnet 3270, DLC 802.2, Token Ring, Integrated Ethernet, Wireless communication enabled (if available)
40 column graphics thermal journal printer paper width 80mm with rewinder and sensor for end and near to end paper	CERTIFICATIONS
A4 format graphics thermal document printer	EMV 3.1.1 e 4.0 level 1 e 2 Progetto Microcircuito - SIA
SAFE Safe CEN A1 certified Safe CEN A3 certified	REGULATION
SECURITY SYSTEMS Banknotes staining device Gas detection system Time delay locks Antiexplosive system Camera Jitter	EMC-EEC Directives Accessibility: Co.Ge.Ban.(ITALY), CAE(UK), ADA(USA), CSA(CANADA).
Badge reader sensors for extraneous bodies Antiskimming Back view mirrors	MULTIMEDIA
	Stereo loudspeaker, sound jack, audio guide. Customizable page and advertisement
	INSTALLATION
	Lobby (Indoor) Fully frontal access
	POWER
	Power: 110÷120 V, 220÷240 V. Frequency: 50÷60 Hz UPS (Uninterruptible Power Supply)
	ENVIRONMENTAL
	Temperature: 0°/+50° Relative humidity: 10÷90%
	DIMENSIONS
	High (H) 1490 mm Width (W) 490 mm Depth (D) 870 mm
	COLOR
	Front panel color customizable