

# SL490

## Lobby ATM

wincash series



- >Small footprint and full functionality
- >Banknotes withdrawal an Web-ATM functions
- >Optimized cash management
- >High resolution 15" TFT LCD colour screen
- >Capabillities to play advertisement with full motion video
- >Industry Standard CEN/XFS architecture
- >User friendly interface, ADA, CAE, CSA and Co.Ge.Ban compliant
- >Multimedia kit for visually impaired people
- >A4 document printer and Barcode reader version available
- >ISO and EMV security compliance with antiskimming and card protection technology



**Kharazmi**  
IT Development Inc.

[www.kharazmico.com](http://www.kharazmico.com)

# TECHNICAL SPECIFICATIONS

USER INTERFACE	CONTROL UNIT
<b>15" TFT LCD color display</b> normal or high luminosity with tamper proof panel	"Intel Pentium IV" or equivalent with DVD and FD
<b>Touch Screen</b>	<b>SOFTWARE ENVIRONMENT</b>
<b>Privacy Display Filter</b>	Microsoft® Windows® XP Professional
<b>8 (4+4) function display keys</b> with integrated led and tactile feedback	<b>SOFTWARE</b>
<b>EPP (Encryption Pin Pad)</b> 16 tamper proof keys (3DES, RSA and Remote Key Loading) PCI certified Compliant with: ISO 9564-1, ISO 13491, ISO 13491-2 and ECBS standard	Middleware: XFS Manager NDC and DDC 91X emulators ISO 8583 WCash-SIA network interface Self Service Banking SW Graphic advertisement SW InfoQul SW Web ATM
<b>Tamper proof QWERTY keyboard</b> with or without Track-ball	Network interface SW: VISA - Europay - Cirrus - Mastercard - Eurocard - Cash Advance - Others
<b>Motorized hybrid badge reader/writer</b> magnetic/microchip (ISO7812/ISO7816) EMV 3.1.1. and 4.0 level 1 certified Card Return on Power Fall Antiskimming jitter (micromovement) Led crown for badge entrance Security sensors for fraud detection Held badge box	Electronic Log with remote transfer SW Distribution
<b>Lighting indicators guide</b> identifying the active peripheral	<b>OPERATOR INTERFACE</b>
<b>BARCODE READER</b>	15" TFT LCD color display + keyboard
<b>BANKNOTES DISPENSER</b>	<b>NETWORKING</b>
1 to 4 cassettes on-site configurable capacity 3000 banknotes each 1 Divert / Retract cassette with separator Staining device, antiexplosive and gas detection device compliant Special design for easy sealing	TCP/IP, SNA/SDLC, X25, Telnet 3270, DLC 802.2, Token Ring, Integrated Ethernet, Wireless communication enabled (if available)
<b>PRINTERS</b>	<b>CERTIFICATIONS</b>
40 column graphics thermal receipt printer paper width 80mm with cutter and sensor for end and near to end paper	EMV 3.1.1 e 4.0 level 1 e 2 Progetto Microcircuito - SIA
40 column graphics thermal journal printer paper width 80mm with rewinder and sensor for end and near to end paper	<b>REGULATION</b>
A4 format graphics thermal document printer	EMC-EEC Directives Accessibility: Co.Ge.Ban.(ITALY), CAE(UK), ADA(USA), CSA(CANADA).
<b>SAFE</b>	<b>MULTIMEDIA</b>
Safe CEN A1 certified Safe CEN A3 certified	Stereo loudspeaker, sound jack, audio guide. Customizable page and advertisement
<b>SECURITY SYSTEMS</b>	<b>INSTALLATION</b>
Banknotes staining device Gas detection system Time delay locks Antiexplosive system Camera Jitter	Lobby (Indoor) Fully frontal access
Badge reader sensors for extraneous bodies Antiskimming Back view mirrors	<b>POWER</b>
	Power: 110÷120 V, 220÷240 V. Frequency: 50÷60 Hz UPS (Uninterruptible Power Supply)
	<b>ENVIRONMENTAL</b>
	Temperature: 0°/+50° Relative humidity: 10÷90%
	<b>DIMENSIONS</b>
	High (H) 1490 mm Width (W) 490 mm Depth (D) 870 mm
	<b>COLOR</b>
	Front panel color customizable